US006711096B1

(12) **United States Patent**
Benjamin

(10) **Patent No.: US 6,711,096 B1**
(45) **Date of Patent: Mar. 23, 2004**

(54) **SHAPED PIEZOELECTRIC COMPOSITE ARRAY**

(75) Inventor: **Kim C. Benjamin**, Portsmouth, RI (US)

(73) Assignee: **The United States of America as represented by the Secretary of the Navy**, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/241,380**

(22) Filed: **Sep. 11, 2002**

(51) **Int. Cl.**[7] **H04R 17/00**

(52) **U.S. Cl.** **367/162**; 367/153; 367/157; 310/337; 310/800

(58) **Field of Search** 367/157, 153, 367/162, 176; 310/800, 327, 340, 367, 337

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,731,763 A	*	3/1988	Wagner	367/153
4,748,366 A	*	5/1988	Taylor	310/800
4,786,837 A	*	11/1988	Kalnin et al.	310/800
4,843,275 A	*	6/1989	Radice	310/334
5,367,501 A	*	11/1994	Kelly et al.	367/157

* cited by examiner

Primary Examiner—Ian J. Lobo
(74) *Attorney, Agent, or Firm*—James M. Kasischke; Michael F. Oglo; Jean-Paul A. Nasser

(57) **ABSTRACT**

An underwater acoustic transducer includes a set of formed substrates of piezoelectric polymer composite, the formed substrates having at least a first and second surface. Conductive electrodes are deposited on the first and second sides of the formed substrates. One surface of the substrate is bonded to an acoustically absorptive backing material. Either surface can be made to conform to a singly or doubly curved geometry. Electrodes deposited on these substrates may be continuous to form a single transducer element, or segmented to form sub-arrays of transducer elements.

7 Claims, 2 Drawing Sheets